



- Πολιουρεθάνη
- Ζάντα από ενισχυμένο ντουραλουμίνιο
- Ρουλεμάν άξονα:
- ☐☐ σφαιρικό [S]



- Cast Polyurethane
- Reinforced aluminum center
- Axle bearing:
- ☐☐ ball [S]



						CODE
100	30	12	41	☐☐	200	WL-100-AO.S12
100S	40	12	40	☐☐	200	WL-100S-AO.S12
		15	47	☐☐	250	WL-100S-AO.S15
100X	50	20	61	☐☐	300	WL-100X-AO.S20
125	30	15	47	☐☐	250	WL-125-AO.S15
125S	50	20	61	☐☐	350	WL-125S-AO.S20
150	40	20	61	☐☐	400	WL-150-AO.S20
160	50	20	61	☐☐	600	WL-160-AO.S20
	50	25	60	☐☐	600	WL-160-AO.S25
180	50	20	60	☐☐	700	WL-180-AO.S20
	50	25	60	☐☐	700	WL-180-AO.S25
200	50	20	61	☐☐	800	WL-200-AO.S20
	50	25	61	☐☐	800	WL-200-AO.S25
250	60	25	60	☐☐	1000	WL-250-AO.S25
	60	30	60	☐☐	1000	WL-250-AO.S30