


**Load Capacity: 60kg, for speed up to 4km/h  
(According to EN 12530)**

|   |                     |                  |                      |
|---|---------------------|------------------|----------------------|
| <br>PRODUCTION OF INSTITUTIONAL CASTORS AND WHEELS<br>THESSALONIKI - GREECE            | PERMIS. VARIATIONS: |                  | PART No:             |
|   | SURFACE FINISH:     |                  | UNF . DIM.:          |
| This drawing is the property of RODA S.A. It must neither be reproduced in any manner nor shall it be submitted to third parties or competitors without our written consent | DESIGNED            | 4/7/2013         | E.POLIMEROPOULOU     |
|   | DRAWN               | 4/7/2013         | E.POLIMEROPOULOU     |
|   | CHECKED             | 4/7/2013         | H.SAATZOGLOU         |
| PART DESCRIPTION :<br><b>Swivel castor, steel support, bolt hole fitting (10,2mm).Wheel 75x24mm,non marking grey rubber (82shA) plain bearing,steel thre</b>                |                     |                  | <b>M.075.TPA.HSG</b> |
| DRAWING NUMBER :  |                     |                  | SHEET No.            |
| QUANTITY  |                     | SCALE            |                      |
| REPLACE :   |                     | GEN. DWG. NUM. : |                      |